

A major purpose of the Technical Information Center is to provide the broadest dissemination possible of information contained in DOE's Research and Development Reports to business, industry, the academic community, and federal, state and local governments.

Although a small portion of this report is not reproducible, it is being made available to expedite the availability of information on the research discussed herein.

LA-UR--83-2367

DE83 017325

TITLE SIMULATION OF TRANSITION CROSSING IN LAMPF II

AUTHOR(S) J. L. Warren and H. A. Thiessen

NOTICE

PORTIONS OF THIS REPORT ARE ILLEGIBLE.

It has been reproduced from the best available copy to permit the broadest possible availability.

SUBMITTED TO The 12th International Conference on High-Energy Accelerators,
Fermi National Accelerator Laboratory, Batavia, IL, Aug. 11-16, 1983

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



By acceptance of this article the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution or to allow others to do so for U.S. Government purposes.

The Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy.

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

J. L. Warren and H. A. Thiessen
Los Alamos National Laboratory, Los Alamos, NM 87545

LAMPF II is the proposed rapid-cycling synchrotron that will take 0.8-GeV protons from the LAMPF linear accelerator and raise them to 32 GeV. Early design models were based on a 60-Hz cycle with 10^{13} protons to be accelerated per cycle. Any reasonable magnetic lattice results in the proton beam going through a phase transition. A general accelerator-simulation code that includes the effect of longitudinal space charge, ARCHSIM, has been used to study the transition in a typical achromatic lattice. The beam remains stable through the transition.

A proposal is in preparation for a 32-GeV rapid-cycling proton synchrotron (LAMPF II) that will be injected with 0.8-GeV protons from LAMPF. Details of the proposed accelerator are given elsewhere in these proceedings.¹ LAMPF is a 120-Hz machine. LAMPF II is being designed for 16×10^{14} protons/s, which means either 10^{12} at 60 Hz or 2×10^{13} at 30 Hz. Either would result in roughly 200-300 bunches spread around a 170-m-radius ring. Each bunch would contain $\sim 10^{11}$ protons. Space-charge effects could be important, especially near the phase transition. Bunch-length oscillations and longitudinal emittance growth can occur just after transition and could limit the beam intensity.² All of the magnetic lattices studied so far result in a phase transition near 12 GeV. It is probably not reasonable to design a machine without a transition because, even if transition causes problems, there exist several known cures.²

The formula for the energy kick in terms of the rf phase ϕ is

$$\Delta W = - \frac{r m c^2}{\gamma^2} \left(\frac{h}{R} \right)^2 [1 + 2 \ln (b/a)] \frac{d\psi(\varphi)}{d\varphi} L \quad (1)$$

where r_p is the classical proton radius, mc^2 the rest mass energy, $mc^2\gamma$ the proton energy, h the harmonic number, $2\pi R$ the machine circumference, b the beam pipe radius, a the beam radius, λ the linear density of charge along the beam, and L the distance along the ring since the last kick.

Description of ARCHSIM

Figure 1 is a simplified flow chart. The input subroutine loads the computer with general control parameters such as the time to complete an acceleration cycle, number of particles to be used in the simulation, print and plot controls, etc. The emittance of the injected beam is simulated by associating a random 6-D phase-space vector with each injected particle and requiring that vector to be in a certain phase-space ellipsoid. The ellipsoid can be offset from the center of phase space in an oscillatory manner to simulate bumping of the incident beam to increase its emittance and decrease space-charge-force effects. The synchrotron is simulated by a ring with a certain number of nodal points (Fig. 2). At these



^aWork supported by the US Department of Energy.




Fig. 2. Example of accelerator with four nodes.

nodal points a number of things can occur. The particles may be: accelerated (ACC); given a space-charge-force kick (SCK); and/or given a kick from a time-dependent quadrupole (TDQ), a skew quadrupole (SKQ), or an octupole (OCT). At a node, one can make phase-space plots such as those shown in Figs. 3 through 5 (PLT). One also has the option of printing out various kinematic parameters such as turn number, time, momentum, rf voltage, rf phase, relative Laslett tune shifts, etc. (PRT). The linear space-charge distribution used to calculate the space-charge kick also is updated at a node (SCD). Particles that have moved outside the admittance of the beam are also tagged at nodes (LOST). Particles are transported between nodes, using matrices calculated from a second-order transport code such as DIMAT⁴ or TRANSPORT (ADV).⁵ The code presently handles 1000 particles, 100 nodes, and up to 10 different transport matrices between nodes. It could be expanded if installed on a faster, larger computer.

The input subroutine also loads all the transport matrices and makes minor adjustments in the matrix elements to insure that they are symplectic (SYMP). This is important because small errors grow large after 12 000 turns around the ring. A Los Alamos internal report describing this symplectification process is in preparation.⁶ The input subroutine




Fig. 3. Radial phase space after 50 turns, at end of injection.




Fig. 4. Vertical phase space after 50 turns, at end of injection.




Fig. 5. Longitudinal phase space after 50 turns, at end of injection.

also calculates the transition- γ (GFUN) and initializes arrays used in the space-charge calculation (INTSC). One can see from Fig. 1 that the program has provision to examine more closely the region around transition. The rise of the magnetic field during the acceleration cycle is simulated by specifying the synchronous momentum at the end of each advance between nodes (PSUN). The transport matrices do not depend on momentum.

Typical simulations such as the one summarized in the next section take about four hours on the VAX 11/750 system.

Results of a Typical Simulation

Figures 3-5 show the injected beam of 1000 particles with total electric charge of $10^{11}e$. The ring being simulated is shown in Fig. 2. Initially the rf voltage and phase were varied in such a way to prevent a rise in Laslett tune shift at low energies. By 500 turns, the voltage/turn had risen to 14.25 MV.

The phase ϕ changed slowly until transition where it was switched to $(\pi - \phi)$.

The longitudinal space-charge distribution and kick are shown in Fig. 6 at 500 turns. The maximum space-charge kick represents $\sim 0.4\%$ of the rf kick. Transition occurred during the 1330th turn. The longitudinal phase-space distribution becomes quite narrow (Fig. 7). Maximum space-charge kick rose to 1.1% of the rf kick. After transition, the rf phase increased slowly toward π at the end of the cycle. Nothing dramatic happens. Figure 8 shows longitudinal phase space at 2000 turns ($E = 16.9$ GeV).




Fig. 6. Longitudinal space-charge density and space-charge energy kick vs rf phase after 500 turns.




Fig. 7. Longitudinal phase space at transition, 1330 turns.




Fig. 8. Longitudinal phase space after 2000 turns.

Acknowledgments

We would like to thank R. K. Conper for supplying a nearly complete subroutine for calculating longitudinal space-charge kicks.

References

1. H. A. Thiessen, Proc. 12th Int. Conf. on High-Energy Accelerators, Fermi National Accelerator Laboratory, Batavia, IL, August 11-16, 1983.
2. A. Sorensen, Particle Accelerators 6, p. 141 (1975).
3. V. K. Neil and A. M. Sessler, Rev. Sci. Instru. 36, p. 429 (1965).
4. R. Servranckx, Proc. 11th Int. Conf. on High-Energy Accelerators, Geneva, Switzerland, July 7-11, 1980, p. 656 (1980).
5. K. L. Brown, Adv. Particle Phys. 1, p. 71 (1967).
6. E. Forest and J. L. Warren, "Application of Symplectic Conditions to Second Order Transport Theory," Los Alamos National Laboratory, Accelerator Technology Division, Group AT-6 Internal report ATN-83-17.